

JF-ADVR-F7216-V2/F7232

16ch/32ch Fribrid 1080P 4HDD ADVR



Features

- ◆ Support 16ch/32ch 1080P Unreal-time Encoding
- ◆ Support AHD/TVI/CVI/CVBS/IP Self-adaptive
- ◆ HDMI/VGA Simultaneous Video Output
- ◆ Support DHCP,FTP,DNS,DDNS,NTP,UPNP,EMAIL,3G,WIFI
- ◆ Support ONVIF Protocol
- ◆ Support WEB,VMS,MYEYE Platform
- ◆ Support Mobile Phone Monitoring(IOS ,Android)
- ◆ Cloud Services,P2P,Alarm Information Push To Phone
- ◆ Support Multi-Language

Dimensions



JF-ADVR-F7216-V2/F7232

16ch/32ch Fribrid 1080P 4HDD ADVR

Specification

4HDD			
Model	JF-ADVR-F7216-V2	JF-ADVR-F7232	
Video			
Encode	16CH*1080P@12fps	32CH*1080P@15fps	
Playback	16CH*1080P@12fps	16CH*1080P@15fps	
Multi-Mode	Analog	16CH*1080P/16CH*1080N	32CH*1080P
	Hybrid	8CH*1080P(Analog)+8CH*1080P(IP)	
	IP	8CH*1080P+8CH*960P/8CH*3M /4CH*5M	32CH*1080P/16CH*3M /8CH*5M
Video Compression	H.264/H.264+		
Audio			
Audio Compression	G.711A		
Interface			
Video Input	16*BNC	32*BNC	
Video Output	1*HDMI,1*VGA		
Audio I/O	16/1		
Alarm I/O	16/4		
Ethernet	1*10/100Mbps Ethernet port, RJ45 port	1*10/100M/1000Mbps Ethernet port, RJ45 port	
PTZ Control	1*RS485, Support for multiple PTZ protocol	1*RS485,1*RS232, Support for multiple PTZ protocol	
USB	3*USB2.0		
Max HDD	4×8TB		
General			
Temperature	0 °C - + 55 °C		
Humidity	10% -90% RH		
Power supply	12V/6A		
Consumption	<15W(Without HDD)		
Dimension	440mm(L)* 400.5mm(W)* 60mm(H)		

JF TECH Co.,Ltd.

Headquarters(Hangzhou):

Building 9, Yinhu Innovation Center, Hangzhou, China

Business Center(Shenzhen):

A 7th Floor, Block Sakata 5 Avenue and Chong Hing Times Tower Shenzhen

All Rights Reserved • Specifications subject to change without notice.

Website:<http://www.jftech.com>

Tel:+86-0571-23271188

Tel:+86-0755-32898088